


NOTES:

1. IF ANY PORTION OF THE MEMBRANE FLASHING DETAIL IS TO BE LEFT EXPOSED, FLEX-FLASH UN IN BONDING ADHESIVE, FLEX-FLASH MB OR HYDROSEAL FLASHING RESIN MUST BE USED (DETAIL LEFT). MM6125-FR MAY BE EXTENDED FULL HEIGHT AS THE FLASHING WHEN THE DETAIL IS TO BE COMPLETELY COVERED (DETAIL RIGHT). REF. DETAILS R-12 AND R-13.
2. FLEX-FLASH F MAY BE USED AT ALL CONCRETE-TO-CONCRETE AND CONCRETE-TO-CONCRETE BLOCK TRANSITIONS. FLEX-FLASH UN MUST BE USED AT ALL OTHER TRANSITIONS (i.e., CONC.-TO-GYP. BOARD, GYP. BOARD-TO-GYP. BOARD, ETC.).



Monolithic Membrane 6125-FR
ROOFING SYSTEMS

AMERICAN HYDROTECH, INC.

TYPICAL TIE-IN DETAILS (THRU-WALL/AIR BARRIER)

SCALE: NONE DATE: 06/01/19	R-17C
-------------------------------	-------

This information is intended only for general conceptual purposes. It is based on data and knowledge considered to be true and correct. It is offered for the user's consideration, investigation and verification and is not intended to substitute for the advice provided by appropriate professionals. Hydrotech assumes no liability for the use of this information. The determination of the suitability and applicability of this information is the sole responsibility of the user.