



NOTES:

1. IF STYROFOAM INSULATION IS USED, IT MUST BE 60 PSI (COMPRESSIVE STRENGTH) BOARD MINIMUM.
2. THE FIXED HEIGHT PEDESTAL SHOWN IS 1/2 A TYPICAL UNIT, WITH THE TRANSVERSE SPACER LUGS LEFT INTACT TO MAINTAIN THE JOINT SPACE AT TERMINATION.
3. REFER TO APPLICABLE MM6125-FR ROOFING OR WATERPROOFING GUIDELINE DETAILS FOR PROPER MEMBRANE/FLASHING DETAILS AND ALTERNATIVES
4. VARIOUS ADJUSTABLE PEDESTAL SYSTEMS ARE AVAILABLE, ALLOWING HEIGHT ADJUSTMENTS >2" - SOME HAVE INTEGRAL JOINT SPACERS, ELIMINATING THE NEED FOR FIXED HEIGHT PEDESTALS ON TOP.
5. ADJUSTMENTS FOR SLOPE CAN BE MADE IN A NUMBER OF WAYS DEPENDING UPON THE ADJUSTABLE PEDESTAL SYSTEM USED. SHIMS ARE USED FOR MINOR LEVEL ADJUSTMENTS.



ULTIMATE ASSEMBLY

AMERICAN HYDROTECH, INC.

| | |
|--|------|
| TYP. TERM. W/ADJUST. PEDESTAL AT WALL/PARAPET/CURB | |
| SCALE: NONE DATE: 11/06/20 | UA-2 |

This information is intended only for general conceptual purposes. It is based on data and knowledge considered to be true and correct. It is offered for the user's consideration, investigation and verification and is not intended to substitute for the advice provided by appropriate professionals. Hydrotech assumes no liability for the use of this information. The determination of the suitability and applicability of this information is the sole responsibility of the user.