

Hydrotech® Flex-Flash F

formerly known as Flex-Flash F



BUILDING TRUST



GENERAL DESCRIPTION

Flex-Flash F is a spunbonded polyester fabric.

BASIC USE

Flex-Flash F is designed to be used as the standard reinforcement material for Hydrotech's Monolithic Membrane 6125® roofing and waterproofing membrane. It is used to reinforce the membrane over cracks, construction joints and changes-in-plane. It is also used in between layers of MM6125® over the entire substrate area to form the "FR" or fabric reinforced assembly.

Flex Flash F is not intended to be used as drains, expansion joints, or as an exposed flashing.



PRODUCT INFORMATION

Flex-Flash F is available in white with standard widths of 6, 12 and 39 inches and the standard length of 600 feet. Store Flex-Flash F in dry conditions and never allow it to get wet.

TECHNICAL DATA

PROPERTY	TEST METHOD	RESULTS
UNIT WEIGHT (oz/sq yd)	ASTM D1910	1.35
% ELONGATION (to break)	ASTM D2523	42
TEAR STRENGTH (lb)	ASTM D2263	8
BREAKING STRENGTH (lb)	ASTM D2523	25
DE MATIA FLEX CYCLES	ASTM D813	100,000

(values published are min. req)

LEED INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Old Hickory, TN
Extraction/Harvesting Location		Old Hickory, TN

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.