

Hydrotech® Root Stop Tape

formerly known as Root Stop Tape



BUILDING TRUST



GENERAL DESCRIPTION

Root Stop Tape is a white, single-sided tape combining a weather-resistant polyethylene backing with an aggressive rubber adhesive.

BASIC USE

Root Stop Tape is designed to be used in Hydrotech’s Garden Roof® Assembly to seal the laps between sheets of Hydrotech’s Root Stop, Root Stop HD, and Root Stop Bamboo root barrier membranes.



INSTALLATION

Before application, the Root Stop membranes must be dry and clean of all potential contaminants in the areas where the Root Stop Tape will be applied. In ambient temperatures below 50°F, Root Stop Tape should be stored at room temperature just prior to use.

TECHNICAL DATA

THICKNESS mils (mm)	9 (0.23)
ADHESIVE STRENGTH oz/inch (g/mm)	30 (33.5)
SERVICE TEMPERATURE °F (°C)	-40 to +180 (-40 to 82.2)
SIZE	4 in. (101.6mm) wide by 210 ft (64 m) long

LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Franklin, MA
Extraction/Harvesting Location		Franklin, MA

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKAs Technical Service Department at 1-800-933-7452. Nothing contained in any SIKAs literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKAs product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKAs product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKAs products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.