

# Hydrotech LiteTop® Aggregate



A SIKA COMPANY

## GENERAL DESCRIPTION

Hydrotech LiteTop Aggregate is an expanded, lightweight aggregate (i.e., expanded shale, clay, slate, pumice and scoria).

## BASIC USE

Hydrotech LiteTop Aggregate is used to fill the cups of Hydrotech’s Gardendrain® GR30 and GR50 elements, as required, to enhance available water holding capacity for plant root systems and to increase compressive strength of the Gardendrain component.



## INSTALLATION

Vollume to Fill (GR30): 2 CY per 1,000 sq.ft.  
 Vollume to Fill (GR50): 3 CY per 1,000 sq.ft.

## TECHNICAL DATA

SIZE GRADATION: Nominally 3/8” (depending on blender locality)

## LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	Varies regionally, contact Hydrotech	
Manufacture Location	40+ locations, contact Hydrotech for more information	
Extraction/Harvesting Location	40+ locations, contact Hydrotech for more information	
VOC Content (g/L)	0	

### Note to Designers:

The information in this product data sheet is general in nature and is not intended to be a stand-alone document to describe Hydrotech’s LiteTop Aggregate. This product data sheet must be used in combination with test results for the locally available LiteTop Aggregate for the project.

**Contact Hydrotech for further information.**

This information is intended only for general conceptual purposes. It is based on data and knowledge considered to be true and correct. It is offered for the user’s consideration, investigation and verification and is not intended to substitute for the advice provided by appropriate professionals. Hydrotech assumes no liability for the use of this information. The determination of the suitability and applicability of this information is the sole responsibility of the user.