

# Hydrotech® Monolithic Membrane 7800 Primer LS



BUILDING TRUST



formerly known as Monolithic Membrane 7800 Primer LS

## GENERAL DESCRIPTION

A low solvent, SBS polymer modified, asphalt primer. Tough, flexible, adhesive and cohesive film is easy to apply and complies with V.O.C. regulations. Elastomeric - moves with substrate.

## BASIC USE

The MM 7800 Primer LS is used to prime all substrate surfaces to receive Hydrotech's Monolithic Membrane 7800 including concrete, wood and metal.

## ADVANTAGES

- Easy to apply.
- Tough, flexible, adhesive and cohesive film.
- Elastometric - moves with substrate
- Complies with current V.O.C. regulations.

## APPLICATION

- All surfaces to be treated with MM7800 Primer must be clean, dry and free from dust, dirt, rust, grease and oil.
- The MM7800 Primer may be brushed, rolled, or sprayed to provide a thin, uniform, film at a rate of 1 gallon per 100 square feet.
- The MM7800 Primer must be allowed sufficient time to thoroughly dry. Recommended: 2 - 4 hours @ 70 degrees F and 24 hours @ 40 degrees F. Cure time may increase at lower temperatures.
- The MM7800 Primer must not be thinned.

## CAUTIONS

Do not smoke or use near fire, flame or electrical sparks. If interior areas are to be coated, arrange for adequate ventilation. Avoid breathing solvent fumes and prolonged contact with skin. See MSDS for further information.

## LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Clark, NJ
Extraction/Harvesting Location		Clark, NJ

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKAs Technical Service Department at 1-800-933-7452. Nothing contained in any SIKAs literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKAs product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKAs product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKAs products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.