

VM Masticseal



A SIKA COMPANY

GENERAL DESCRIPTION

VM Masticseal is a rubberized asphalt mastic sealant.

BASIC USE

VM Masticseal is used to seal all termination edges, cut edges and seam "T" joints of Hydrotech's VM 60 sheet waterproofing membrane.

APPLICATION

- A 1/2 - 1 inch wide bead of Masticseal should be applied at all VM 60 sheet membrane edges that required cutting (flashings, adjacent field sheets), all horizontal sheet termination edges (top and bottom of wall/footing) and along all seam edges (horizontal and vertical) that occur at the junction of the wall and footing.
- VM Masticseal should be applied to all sheet terminations at the end of each days work.

CONTAINER/WEIGHT

VM Masticseal is available in 5 gallon pails, weighing 48 pounds, and a case of 12 - 30 ounce tubes, weighing 27 pounds per case. The pails will cover approximately 100 feet per gallon with a 1 inch bead. Each tube will cover approximately 65 feet with a 1/2 inch bead.

LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Corsicana, TX
Extraction/Harvesting Location		
VOC Content (g/L)		0

This information is intended only for general conceptual purposes. It is based on data and knowledge considered to be true and correct. It is offered for the user's consideration, investigation and verification and is not intended to substitute for the advice provided by appropriate professionals. Hydrotech assumes no liability for the use of this information. The determination of the suitability and applicability of this information is the sole responsibility of the user.