



Hydrotech[®] VM Precoat Adhesive

formerly known as VM Precoat Adhesive

GENERAL DESCRIPTION

VM Precoat Adhesive is a fast drying, high-tack, rubber based adhesives in solution.

BASIC USE

VM Precoat Adhesive is used to prime acceptable substrates prior to the application of Hydrotech’s VM 60 sheet waterproofing membrane.

APPLICATION

- Areas to receive the VM Precoat Adhesive should be clean and dry and free of any contaminants. VM Precoat Adhesive should not be applied to areas that will receive the VM Liquid Membrane.
- VM Precoat Adhesive should be stirred before use.
- VM Precoat Adhesive should be applied, by brush or short nap roller, to all substrate surfaces to receive Hydrotech’s VM 60 sheet waterproofing membrane.
- Apply only as much VM Precoat Adhesive as will be covered with the sheet membrane within the same day. Primed areas left overnight will require re-priming.
- Allow the VM Precoat Adhesive time to dry (typically 20 - 30 minutes) prior to installing the VM 60 sheet waterproofing membrane. The adhesives will retain an aggressively tacky surface.

LIMITATIONS/PRECAUTIONS

- VM Precoat Adhesive is a red-labeled product. Do not use near open flame. Avoid breathing vapors and prolonged contact with skin.
- When used in confined spaces (i.e., bottom of foundation wall excavation) mechanical ventilation is required.

CONTAINER/WEIGHT

VM Precoat Adhesive is available in 5 gallon pails that weigh 37 pounds/pail. Precoat Adhesives should be applied at a rate of 250 - 350 square feet per gallon.

LEED[®] INFORMATION

| | Credit 4 | Credit 5 |
|--------------------------------|----------|---------------|
| Recycled Content (% by weight) | 0 | |
| Manufacture Location | | Corsicana, TX |
| Extraction/Harvesting Location | | |

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKAs Technical Service Department at 1-800-933-7452. Nothing contained in any SIKAs literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKAs product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKAs product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKAs SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKAs SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKAs products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.