

VM Precoat Adhesive



A SIKA COMPANY

GENERAL DESCRIPTION

VM Precoat Adhesive is a fast drying, high-tack, rubber based adhesives in solution.

BASIC USE

VM Precoat Adhesive is used to prime acceptable substrates prior to the application of Hydrotech’s VM 60 sheet waterproofing membrane.

APPLICATION

- Areas to receive the VM Precoat Adhesive should be clean and dry and free of any contaminants. VM Precoat Adhesive should not be applied to areas that will receive the VM Liquid Membrane.
- VM Precoat Adhesive should be stirred before use.
- VM Precoat Adhesive should be applied, by brush or short nap roller, to all substrate surfaces to receive Hydrotech’s VM 60 sheet waterproofing membrane.
- Apply only as much VM Precoat Adhesive as will be covered with the sheet membrane within the same day. Primed areas left overnight will require re-priming.
- Allow the VM Precoat Adhesive time to dry (typically 20 - 30 minutes) prior to installing the VM 60 sheet waterproofing membrane. The adhesives will retain an aggressively tacky surface.

LIMITATIONS/PRECAUTIONS

- VM Precoat Adhesive is a red-labeled product. Do not use near open flame. Avoid breathing vapors and prolonged contact with skin.
- When used in confined spaces (i.e., bottom of foundation wall excavation) mechanical ventilation is required.

CONTAINER/WEIGHT

VM Precoat Adhesive is available in 5 gallon pails that weigh 37 pounds/pail. Precoat Adhesives should be applied at a rate of 250 - 350 square feet per gallon.

LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Corsicana, TX
Extraction/Harvesting Location		
VOC Content (g/L)		0

This information is intended only for general conceptual purposes. It is based on data and knowledge considered to be true and correct. It is offered for the user’s consideration, investigation and verification and is not intended to substitute for the advice provided by appropriate professionals. Hydrotech assumes no liability for the use of this information. The determination of the suitability and applicability of this information is the sole responsibility of the user.