

HydroSeal Fleece



BUILDING TRUST



GENERAL DESCRIPTION

HydroSeal Fleece is non-woven, chopped strand polyester fabric reinforcement.

BASIC USE

HydroSeal Fleece is used to reinforce HydroSeal Resin cold, fluid-applied, flashing membrane to improve tear strength, puncture resistance, and crack bridging capabilities while maintaining membrane uniformity.

PACKAGING/SIZES/COVERAGE

HydroSeal Fleece is supplied in 8, 14, 20, and 41 inch wide X 164 foot (50 m) rolls. Always store in cool and dry location. Store flat to avoid deforming rolls and creasing fabric. Allow for 2 inch (5 cm) overlap at side laps, 4 inch (10 cm) overlap at end laps, 4 inch overlap at all flashings, and an additional 5% for waste.

PRECAUTIONS

HydroSeal Fleece may be disposed of in standard landfills.

TECHNICAL DATA

PROPERTY	RESULTS
COLOR	White
NOMINAL THICKNESS (mils)	30 - 40 mils
WEIGHT (g/sqm)	10
TENSILE STRENGTH @ BREAK (N/50 mm)	≥ 130 Long. ≥ 150 Transv.
ELONGATION (%)	≥ 50 Long. ≥ 70 Transv.
TEAR RESISTANCE (daN)	> 20
PUNCTURE STRENGTH (daN)	> 24
WATER ABSORPTION (%)	< 1

This information is intended only for general conceptual purposes. It is based on data and knowledge considered to be true and correct. It is offered for the user's consideration, investigation and verification and is not intended to substitute for the advice provided by appropriate professionals. Hydrotech assumes no liability for the use of this information. The determination of the suitability and applicability of this information is the sole responsibility of the user.