

Hydrotech® HydroSeal Activator Cleaner



BUILDING TRUST



formerly known as HydroSeal Activator Cleaner

GENERAL DESCRIPTION

HydroSeal Activator is clear aromatic blended solvent.

BASIC USE

HydroSeal Activator is used to clean and reactivate the transition area of existing cured in-place membranes at tie-ins, repairs and between staged coats of resin. HydroSeal Activator may also be used as solvent for cleaning metal and plastic surfaces prior to resin application, or for cleaning spills, tools and equipment.

APPLICATION

HydroSeal Activator should be wiped on the in-place membrane, allowed 20 minutes evaporation time, and overcoated within 60 minutes of application. HydroSeal Activator should only be applied over an area that can be overcoated within a 60 minute period. Re-apply HydroSeal Activator as required to assure proper reactivation of all transition areas.

PACKAGING/SIZES/COVERAGE

HydroSeal Activator is supplied in 1 gallon and 5 gallon re-sealable metal cans.

Consumption will vary depending upon application and use.

Always store in a cool and dry location. Do not store in direct sunlight or in temperatures below 32°F(0°C) or above 77°F(25°C). Approximate shelf life is 12-months when left sealed and with proper storage.

PRECAUTIONS

Refer to product Material Safety Data Sheet (MSDS) prior to use or handling.

Always store in cool and dry location. Do not store in direct sunlight or in temperatures above 77°F (25°C). Flammable, keep away from heat, sparks, open flame.

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.