



NOTES:

1. DESIGNER MUST SPECIFY APPROPRIATE ROOTSTOP MATERIALS TO ACCOMMODATE DESIRED PLANT MATERIALS.
2. FIXED HEIGHT AND ADJUSTABLE PEDESTALS NECESSARY FOR AN OPEN-JOINT PAVER INSTALLATION CANNOT BE INSTALLED OVER GARDENDRAIN. THE GARDEN ROOF AND ULTIMATE ASSEMBLY INSTALLATIONS SHOULD BE DIVIDED.
3. IF GARDENDRAIN ELEMENTS ARE INSTALLED UNDER HARDSCAPE AREAS THE CUPS MUST BE FILLED WITH LIGHTWEIGHT EXPANDED AGGREGATE. GARDENDRAIN MAY ALSO BE USED AS FORMS FOR SETTING CONCRETE FOOTINGS FOR CURBS, ETC.
4. REFER TO APPLICABLE MM 6125-FR ROOFING OR WATERPROOFING GUIDELINE DETAILS FOR PROPER MEMBRANE/FLASHING DETAILS AND ALTERNATIVES.



GARDEN ROOF ASSEMBLY

AMERICAN HYDROTECH, INC.

POSSIBLE TRANSITION OPTION - CMU WITH VENEER OPTION - (INTENSIVE APPLICATION DEPICTED)

SCALE: NONE DATE: 11/01/17	GA-5G
-------------------------------	-------