

Hydrotech® Hydrodrain® Max

formerly known as Hydrodrain® Max



BUILDING TRUST



GENERAL DESCRIPTION

Hydrodrain Max is a roll product consisting of an entangled polypropylene mesh with a light fabric backing.

BASIC USE

Hydrodrain Max is used in Hydrotech’s Rock Mineral Wool assembly in conjunction with Rock Mineral Wool and LiteTop® engineered growing media to create a Garden Roof® Assembly with higher water holding capacities. Hydrodrain Max does not store water; it is designed to provide a pathway for air and water below the Rock Wool.



INSTALLATION

- Refer to Hydrotech’s GW series Rock Mineral Wool Details for specific installation requirements.
- Hydrodrain Max should be stored out of direct sunlight whenever possible.
- Hydrodrain Max should be covered with Rock Mineral Wool and LiteTop Growing Media as soon as possible, but no longer than seven (7) days of installation.

TECHNICAL DATA

ROLL DIMENSIONS:	3.25 feet x 153.8 feet (500 square feet)
THICKNESS:	0.775 inch (approx.)
DENSITY:	16 oz per square yard
ROLL WEIGHT:	61 pounds (approx.)
ROLL DIAMETER:	42.5 inches (approx.)
FLOW RATE (ASTM D4716):	9.1 gal/min./feet; h.g.=0.13

LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	40 (pi)	
Manufacture Location		Alpharetta, GA
Extraction/Harvesting Location		Alpharetta, GA

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.